

# Ferrnsol<sup>™</sup> Welding Anti-Spatter

P R O D U C T D A T A

# **DESCRIPTION**

**Ferrnsol Welding Anti-spatter** is a water based formula designed to prevent the adhesion of welding spatter. It provides a protective coating to help aid with removal of weld spatter and helps keep welding tips and nozzles clean.

### **USES**

- Use on welding area surfaces where weld spatter could be a problem
- Excellent choice for use in automatic spray equipment or handheld spray bottles

### **ADVANTAGES**

- Eliminates spatters on welding equipment
- Reduces downtime with easy clean-up
- Improves weld quality
- Increases tool life
- Phosphate-free
- Silicone-free

DIRECTION	IS
-----------	----

Make sure working surface is clean and dry. Spray a thin layer of Ferrnsol Welding Anti-Spatter onto work area uniformly to assure proper coverage.

Product Data			
Form: Liquid	Odor: Mild	Color: Red	
Solubility in Water: Complete			
Typical pH: 10			
Specific Gravity/ Density : 1.02 / 8.5			
Melting / Freezing Point: ~ 20°F			

# **CLEANUP**

Clean tools and equipment with clean soapy water

# **STORAGE**

Store in tightly sealed containers in a cool dry area away from direct sunlight and sources of heat. Shelf life of properly stored material is one year from date of manufacture.

## **PRECAUTIONS**

Causes serious eye irritation. In case of eye contact, flush immediately with water.

If swallowed rinse mouth immediately and call poison center/ doctor if you feel unwell.

Can cause mild skin irritation, wash skin with soap and water.

Packaging and Part Number			
4 x 1 gal case	F3.0130		
5 gal (207.9L) pail	F3.0131		
55 gal (207.9L) drums	F3.0125		

Updated: 2023